



## TECHNICAL INFORMATIONS

# TUBO T8 LED STANDARD

## 9W 6500K 2 LADOS

Tubo de vidro Standard com conexão nos dois topos e 110 LM / W.

Standard glass tube with double side connection and 110 LM / W.

Tubo Standard de Cristal Glass, con conexión en los dos lados y 110 LM / W.

**ILAR-00282**




| REFERENCE                          |                 | DIMENSION & WEIGHT     |            | PHOTOMETRICAL DATA     |         |
|------------------------------------|-----------------|------------------------|------------|------------------------|---------|
| Base                               | G13             | Tube Diameter          | 26mm       | Total Luminous Flux    | 990lm   |
| Body Type                          | GLASS           | Length                 | 600mm      | Luminous Efficacy      | 110lm/W |
| Conection to Power                 | Dual Ended - 2P | Weight                 | 120g       | Beam Angle             | 320°    |
| Nominal Lifetime (EOL end of life) | 25000H          | Packaging Unit         | 25PCS      | Colour Temperature     | 6500K   |
| Switching Cycle (times)            | 50000X          | Dimensions (L x W x H) | 64x20x20cm | Colour Rendering Index | >80     |
| Dimmable                           | NO              | Gross Weight           | 5.6kg      |                        |         |
| Mercury Free                       | YES             | Volume                 | 0.0256     |                        |         |
| Microwave Sensor                   | NO              |                        |            |                        |         |
| Plastic Proteccion                 | NO              |                        |            |                        |         |

| ELECTRICAL AND OPERATING DATA |                   | ENERGY LABEL & STANDARS      |      | CERTIFICATIONS |     |
|-------------------------------|-------------------|------------------------------|------|----------------|-----|
| Rated Voltage                 | 9W                | Energy Label                 | A+   | CE Marking     | -   |
| Nominal Wattage               | 9W                | Energy Consumption KWH/1000H | 9kWh | ROHS           | YES |
| Nominal Current               | 0.078A            | Type of Protection           | IP20 | ENEC           | YES |
| Nominal Voltage               | 180-265V          |                              |      |                |     |
| Operating Frequency           | 50/60Hz           |                              |      |                |     |
| Type of Current               | AC                |                              |      |                |     |
| Power Factor                  | 0.5               |                              |      |                |     |
| Starting Time                 | 0.05s             |                              |      |                |     |
| Warm - Up Time (60%)          | 0.5s              |                              |      |                |     |
| Operating Temperature         | -20° C to + 45° C |                              |      |                |     |

### SIZE

### BEAM ANGLE



Designed by Aron Light in Portugal. Made in PRC

