



## TECHNICAL INFORMATIONS

# TUBO T8 LED STANDARD

## 9W 3000K LN

Tubo de vidro Standard com conexão em um só topo e 110 LM / W.

Standard glass tube with single side connection and 110 LM / W.

Tubo Standard de Cristal Glass, con conexión por un lados y 110 LM / W.

**ILAR-00289**



### REFERENCE

Base	G13
Body Type	GLASS
Conection to Power	Single Ended - 1P
Nominal Lifetime (EOL end of life)	25000H
Switching Cycle (times)	50000X
Dimmable	NO
Mercury Free	YES
Microwave Sensor	NO
Plastic Proteccion	NO

### DIMENSION & WEIGHT

Tube Diameter	26mm
Length	600mm
Weight	120g
Packaging Unit	25PCS
Dimensions (L x W x H)	67x20x20cm
Gross Weight	5.6kg
Volume	0.0256

### PHOTOMETRICAL DATA

Total Luminous Flux	990lm
Luminous Efficacy	110lm/W
Beam Angle	320°
Colour Temperature	3000K
Colour Rendering Index	>80

### ELECTRICAL AND OPERATING DATA

Rated Voltage	9W
Nominal Wattage	9W
Nominal Current	0.078A
Nominal Voltage	180-265V
Operating Frequency	50/60Hz
Type of Current	AC
Power Factor	0.5
Starting Time	0.05s
Warm - Up Time (60%)	0.5s
Operating Temperature	-20° C to + 45° C


### ENERGY LABEL & STANDARS

Energy Label	A+
Energy Consumption KWH/1000H	9kWh
Type of Protection	IP20

### CERTIFICATIONS

CE Marking	-
ROHS	YES
ENEC	YES

### SIZE



### BEAM ANGLE

Designed by Aron Light in Portugal. Made in PRC

