

TECHNICAL INFORMATIONS

GU10 38° SPOTLIGHTS

6W 3000K

Linha GU10 com vários ângulos de abertura e potências para diferentes espaços.

GU10 line with several wattages and beam angles for different spaces.

Línea microicas con diferentes potencias y haz de luz para espacios variados.

ILAR-00550



REFERENCE

| | |
|------------------------------------|------------|
| Reference | ILAR-00550 |
| Lamp type | GU10 |
| Lamp Base | GU10 |
| Nominal Lifetime (EOL end of life) | 25000h |
| Switching Cycle (times) | 15000X |
| Dimmable | No |
| Mercury Free | Yes |

DIMENSION & WEIGHT

| | |
|----------|------|
| Diameter | 50mm |
| Length | 55mm |
| Weight | 30g |

PHOTOMETRICAL DATA

| | |
|------------------------|--------|
| Total Luminous Flux | 450lm |
| Luminous Efficacy | 80lm/W |
| Beam Angle | 38° |
| Colour Temperature | 3000K |
| Colour Rendering Index | 80 |
| Colour Consistency | <= 6 |

ELECTRICAL AND OPERATING DATA

| | |
|-----------------------|-----------------|
| Power Rated | 6W |
| Equivalent Wattage | 41W |
| Lamp Current | 45mA |
| Nominal Voltage | 220-240V |
| Operating Frequency | 50/60Hz |
| Power Factor | 0.5 |
| Starting Time | 0.5s |
| Warm-up Time (60%) | 0.5s |
| Operating Temperature | -30°C to + 40°C |


ENERGY LABEL & STANDARS

| | |
|------------------------------|------|
| Energy Label | A+ |
| Energy Consumption KWH/1000H | 6kWh |


CERTIFICATIONS

| | |
|------|-----|
| ROHS | YES |
| CE | YES |
| LM70 | NO |
| LM80 | YES |
| LM79 | - |
| TM21 | - |
| ENEC | - |

SIZE



BEAM ANGLE



Designed by Aron Light in Portugal. Made in PRC

