

TECHNICAL INFORMATION

TUBO T8 LED STANDARD

9W 3000K LN

Tubo de vidro Standard com conexão em um só topo e 110 LM / W.

Standard glass tube with single side connection and 110 LM / W.

Tubo Standard de Cristal Glass, con conexión por un lados y 110 LM / W.


ILAR-00289



REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Base	G13	Tube Diameter	26mm	Total Luminous Flux	990lm
Body Type	GLASS	Length	600mm	Luminous Efficacy	110lm/W
Conection to Power	Single Ended - 1P	Weight	120g	Beam Angle	320°
Nominal Lifetime (EOL end of life)	25000H	Packaging Unit	25PCS	Colour Temperature	3000K
Switching Cycle (times)	50000X	Dimensions (L x W x H)	67x20x20cm	Colour Rendering Index	>80
Dimmable	NO	Gross Weight	5.6kg		
Mercury Free	YES	Volume	0.0256		
Microwave Sensor	NO				
Plastic Protection	NO				

ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARS		CERTIFICATIONS	
Rated Voltage	9W	Energy Label	A+	CE Marking	-
Nominal Wattage	9W	Energy Consumption KWH/1000H	9kWh	ROHS	YES
Nominal Current	0.078A	Type of Protection	IP20	ENEC	YES
Nominal Voltage	180-265V				
Operating Frequency	50/60Hz				
Type of Current	AC				
Power Factor	0.5				
Starting Time	0.05s				
Warm - Up Time (60%)	0.5s				
Operating Temperature	-20° C to + 45° C				

SIZE



BEAM ANGLE

Designed by Aron Light in Portugal. Made in PRC



TECHNICAL INFORMATION

TUBO T8 LED STANDARD

9W 4500K LN

Tubo de vidro Standard com conexão em um só topo e 110 LM / W.

Standard glass tube with single side connection and 110 LM / W.

Tubo Standard de Cristal Glass, con conexión por un lados y 110 LM / W.


ILAR-00290



REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Base	G13	Tube Diameter	26mm	Total Luminous Flux	990lm
Body Type	GLASS	Length	600mm	Luminous Efficacy	110lm/W
Conection to Power	Single Ended - 1P	Weight	120g	Beam Angle	320°
Nominal Lifetime (EOL end of life)	25000H	Packaging Unit	25PCS	Colour Temperature	4500K
Switching Cycle (times)	50000X	Dimensions (L x W x H)	67x20x20cm	Colour Rendering Index	>80
Dimmable	NO	Gross Weight	5.6kg		
Mercury Free	YES	Volume	0.0256		
Microwave Sensor	NO				
Plastic Protection	NO				

ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARS		CERTIFICATIONS	
Rated Voltage	9W	Energy Label	A+	CE Marking	-
Nominal Wattage	9W	Energy Consumption KWH/1000H	9kWh	ROHS	YES
Nominal Current	0.078A	Type of Protection	IP20	ENEC	YES
Nominal Voltage	180-265V				
Operating Frequency	50/60Hz				
Type of Current	AC				
Power Factor	0.5				
Starting Time	0.05s				
Warm - Up Time (60%)	0.5s				
Operating Temperature	-20° C to + 45° C				

SIZE



BEAM ANGLE

Designed by Aron Light in Portugal. Made in PRC



TECHNICAL INFORMATION

TUBO T8 LED STANDARD

9W 6500K LN

Tubo de vidro Standard com conexão em um só topo e 110 LM / W.

Standard glass tube with single side connection and 110 LM / W.

Tubo Standard de Cristal Glass, con conexión por un lados y 110 LM / W.

ILAR-00291



REFERENCE	
Base	G13
Body Type	GLASS
Conection to Power	Single Ended - 1P
Nominal Lifetime (EOL end of life)	25000H
Switching Cycle (times)	50000X
Dimmable	NO
Mercury Free	YES
Microwave Sensor	NO
Plastic Proteccion	NO

DIMENSION & WEIGHT	
Tube Diameter	26mm
Length	600mm
Weight	120g
Packaging Unit	25PCS
Dimensions (L x W x H)	67x20x20cm
Gross Weight	5.6kg
Volume	0.0256


PHOTOMETRICAL DATA	
Total Luminous Flux	990lm
Luminous Efficacy	110lm/W
Beam Angle	320°
Colour Temperature	6500K
Colour Rendering Index	>80

ELECTRICAL AND OPERATING DATA	
Rated Voltage	9W
Nominal Wattage	9W
Nominal Current	0.078A
Nominal Voltage	180-265V
Operating Frequency	50/60Hz
Type of Current	AC
Power Factor	0.5
Starting Time	0.05s
Warm - Up Time (60%)	0.5s
Operating Temperature	-20° C to + 45° C

ENERGY LABEL & STANDARS	
Energy Label	A+
Energy Consumption KWH/1000H	9kWh
Type of Protection	IP20

CERTIFICATIONS	
CE Marking	-
ROHS	YES
ENEC	YES

SIZE



BEAM ANGLE

Designed by Aron Light in Portugal Made in PRC

