

TECHNICAL INFORMATION

TUBO T8 LED STANDARD

22W 6500K LN

Tubo de vidro Standard com conexão em um só topo e 110 LM / W.

Standard glass tube with single side connection and 110 LM / W.

Tubo Standard de Cristal Glass, con conexión por un lados y 110 LM / W.


ILAR-00297



REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Base	G13	Tube Diameter	26mm	Total Luminous Flux	2420lm
Body Type	GLASS	Length	1500mm	Luminous Efficacy	110lm/W
Conection to Power	Single Ended - 1P	Weight	300g	Beam Angle	320°
Nominal Lifetime (EOL end of life)	25000H	Packaging Unit	25PCS	Colour Temperature	6500K
Switching Cycle (times)	50000X	Dimensions (L x W x H)	158x20x20cm	Colour Rendering Index	>80
Dimmable	NO	Gross Weight	12.5kg		
Mercury Free	YES	Volume	0.0616		
Microwave Sensor	NO				
Plastic Proteccion	NO				

ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARS		CERTIFICATIONS	
Rated Voltage	22W	Energy Label	A+	CE Marking	-
Nominal Wattage	22W	Energy Consumption KWH/1000H	22kWh	ROHS	YES
Nominal Current	0.1954A	Type of Protection	IP20	ENEC	YES
Nominal Voltage	180-265V				
Operating Frequency	50/60Hz				
Type of Current	AC				
Power Factor	0.5				
Starting Time	0.05s				
Warm - Up Time (60%)	0.5s				
Operating Temperature	-20° C to + 45° C				

SIZE



BEAM ANGLE

Designed by Aron Light in Portugal Made in PRC



TECHNICAL INFORMATION

TUBO T8 LED STANDARD

22W 4500K LN

Tubo de vidro Standard com conexão em um só topo e 110 LM / W.

Standard glass tube with single side connection and 110 LM / W.

Tubo Standard de Cristal Glass, con conexión por un lados y 110 LM / W.


ILAR-00296



REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Base	G13	Tube Diameter	26mm	Total Luminous Flux	2420lm
Body Type	GLASS	Length	1500mm	Luminous Efficacy	110lm/W
Conection to Power	Single Ended - 1P	Weight	300g	Beam Angle	320°
Nominal Lifetime (EOL end of life)	25000H	Packaging Unit	25PCS	Colour Temperature	4500K
Switching Cycle (times)	50000X	Dimensions (L x W x H)	158x20x20cm	Colour Rendering Index	>80
Dimmable	NO	Gross Weight	12.5kg		
Mercury Free	YES	Volume	0.0616		
Microwave Sensor	NO				
Plastic Proteccion	NO				

ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARS		CERTIFICATIONS	
Rated Voltage	22W	Energy Label	A+	CE Marking	-
Nominal Wattage	22W	Energy Consumption KWH/1000H	22kWh	ROHS	YES
Nominal Current	0.1954A	Type of Protection	IP20	ENEC	YES
Nominal Voltage	180-265V				
Operating Frequency	50/60Hz				
Type of Current	AC				
Power Factor	0.5				
Starting Time	0.05s				
Warm - Up Time (60%)	0.5s				
Operating Temperature	-20° C to + 45° C				

SIZE	BEAM ANGLE
------	------------



Designed by Aron Light in Portugal Made in PRC



TECHNICAL INFORMATION

TUBO T8 LED STANDARD

22W 3000K LN

Tubo de vidro Standard com conexão em um só topo e 110 LM / W.

Standard glass tube with single side connection and 110 LM / W.

Tubo Standard de Cristal Glass, con conexión por un lados y 110 LM / W.


ILAR-00295



REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Base	G13	Tube Diameter	26mm	Total Luminous Flux	2420lm
Body Type	GLASS	Length	1500mm	Luminous Efficacy	110lm/W
Conection to Power	Single Ended - 1P	Weight	300g	Beam Angle	320°
Nominal Lifetime (EOL end of life)	25000H	Packaging Unit	25PCS	Colour Temperature	3000K
Switching Cycle (times)	50000X	Dimensions (L x W x H)	158x20x20cm	Colour Rendering Index	>80
Dimmable	NO	Gross Weight	12.5kg		
Mercury Free	YES	Volume	0.0616		
Microwave Sensor	NO				
Plastic Protection	NO				

ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARS		CERTIFICATIONS	
Rated Voltage	22W	Energy Label	A+	CE Marking	-
Nominal Wattage	22W	Energy Consumption KWH/1000H	22kWh	ROHS	YES
Nominal Current	0.1954A	Type of Protection	IP20	ENEC	YES
Nominal Voltage	180-265V				
Operating Frequency	50/60Hz				
Type of Current	AC				
Power Factor	0.5				
Starting Time	0.05s				
Warm - Up Time (60%)	0.5s				
Operating Temperature	-20° C to + 45° C				

SIZE	BEAM ANGLE
------	------------



Designed by Aron Light in Portugal Made in PRC

