

TECHNICAL INFORMATION

MÓDULO LED

8W 3000K

Novo Módulo e Alta Performance.
New Module and Best Performance.
Nuevo Módulo y Mejor Rendimiento.

ILAR-00553



REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Reference	ILAR-00553	Diameter	Ø50mm	Total Luminous Flux	680lm
Lamp type	Módulo	Length	40mm	Luminous Efficacy	85lm/W
Lamp Base	Módulo	Weight	30g	Beam Angle	310°
Nominal Lifetime (EOL end of life)	25000h			Colour Temperature	3000K
Switching Cycle (times)	15000X			Colour Rendering Index	>80
Dimmable	No			Colour Consistency	-
Mercury Free	Yes				

ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARS		CERTIFICATIONS	
Power Rated	8W	Energy Label	A+	ROHS	YES
Equivalent Wattage	-	Energy Consumption KWH/1000H	8kWh	CE	YES
Lamp Current	55mA			LM70	NO
Nominal Voltage	175-265V			LM80	YES
Operating Frequency	50/60Hz			LM79	-
Power Factor	0.5			TM21	-
Starting Time	0.5s			ENEC	-
Warm-up Time (60%)	0.5s				
Operating Temperature	-30°C to + 40°C				

SIZE	BEAM ANGLE

Designed by Aron Light in Portugal. Made in PRC



TECHNICAL INFORMATION

MÓDULO LED

8W 4500K

Novo Módulo e Alta Performance.
New Module and Best Performance.
Nuevo Módulo y Mejor Rendimiento.

ILAR-00554



REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Reference	ILAR-00554	Diameter	Ø50mm	Total Luminous Flux	690lm
Lamp type	Módulo	Length	40mm	Luminous Efficacy	85lm/W
Lamp Base	Módulo	Weight	30g	Beam Angle	310°
Nominal Lifetime (EOL end of life)	25000h			Colour Temperature	4500K
Switching Cycle (times)	15000X			Colour Rendering Index	>80
Dimmable	No			Colour Consistency	-
Mercury Free	Yes				

ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARS		CERTIFICATIONS	
Power Rated	8W	Energy Label	A+	ROHS	YES
Equivalent Wattage	-	Energy Consumption KWH/1000H	8kWh	CE	YES
Lamp Current	55mA			LM70	NO
Nominal Voltage	175-265V			LM80	YES
Operating Frequency	50/60Hz			LM79	-
Power Factor	0.5			TM21	-
Starting Time	0.5s			ENEC	-
Warm-up Time (60%)	0.5s				
Operating Temperature	-30°C to + 40°C				

SIZE	BEAM ANGLE

Designed by Aron Light in Portugal. Made in PRC



TECHNICAL INFORMATION

MÓDULO LED

8W 6500K

Novo Módulo e Alta Performance.
New Module and Best Performance.
Nuevo Módulo y Mejor Rendimiento.

ILAR-00555



REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Reference	ILAR-00555	Diameter	Ø50mm	Total Luminous Flux	700lm
Lamp type	Módulo	Length	40mm	Luminous Efficacy	85lm/W
Lamp Base	Módulo	Weight	30g	Beam Angle	310°
Nominal Lifetime (EOL end of life)	25000h			Colour Temperature	6500K
Switching Cycle (times)	15000X			Colour Rendering Index	>80
Dimmable	No			Colour Consistency	-
Mercury Free	Yes				

ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARS		CERTIFICATIONS	
Power Rated	8W	Energy Label	A+	ROHS	YES
Equivalent Wattage	-	Energy Consumption KWH/1000H	8kWh	CE	YES
Lamp Current	55mA			LM70	NO
Nominal Voltage	175-265V			LM80	YES
Operating Frequency	50/60Hz			LM79	-
Power Factor	0.5			TM21	-
Starting Time	0.5s			ENEC	-
Warm-up Time (60%)	0.5s				
Operating Temperature	-30°C to + 40°C				

SIZE	BEAM ANGLE

Designed by Aron Light in Portugal. Made in PRC

