

## TECHNICAL INFORMATION

# SILK

## 6W 3000K CINZENTO

Design moderno, chips LED de elevada reprodução, alumínio de fundição injetada, elevados níveis de proteção (IP e IK), forte resistência à corrosão.

Modern design, high-performance LED chips, injected cast aluminum, high protection levels (IP and IK), strong corrosion resistance.

Diseño moderno, chips LED de alto rendimiento, aluminio fundido inyectado, altos niveles de protección (IP e IK), fuerte resistencia a la corrosión.




### ILAR-00819

REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Reference	ILAR-00819	Length	140mm	Total Luminous Flux	85lm
Base	XTE	Width	95mm	Luminous Efficacy	14 lm/W
Body Material	Aluminum	Height	62mm	Beam Angle	3°
Housing Colour	Dark Grey	Packaging Unit	Carton box 18 pcs	Colour Temperature	3000K
Nominal Lifetime (EOL end of life)	15000h	Gross Weight	13 kg	Colour Rendering Index	80
Surface / Recessed	Surface	Volume	25 dm³		
Dimmable	NO				
Installation	Wall				

ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARDS		CERTIFICATIONS	
Nominal Wattage	6W	Energy Label	A	2014/30/EU (EMC Directive)	YES
Nominal Voltage	220-240V	Energy Consumption KWH/1000H	6 kWh	2014/35/EU (LVD Directive)	YES
Operating Frequency	50/60Hz	Type of Protection	IP65	ROHS	YES
Operating Temperature	- 20° C to + 50° C	Protection Class	I	ENEC	NO
Starting Time 100% ON	0.000s	Protection Class IK (shock resistance)	IK10	Warranty	3 YEARS
ON/OFF Cycles	>15000				

### SIZE



### BEAM ANGLE

Designed by Aron Light in Portugal. Made in PRC

