



TECHNICAL INFORMATIONS

ASPEN PAR 30

MAX 75W CINZENTO

Design moderno, chips LED de elevada reprodução, alumínio de fundição injetada, elevados níveis de proteção (IP e IK), forte resistência à corrosão.

Modern design, high-performance LED chips, injected cast aluminum, high protection levels (IP and IK), strong corrosion resistance.

Diseño moderno, chips LED de alto rendimiento, aluminio fundido inyectado, altos niveles de protección (IP e IK), fuerte resistencia a la corrosión.




ILAR-00809

REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Reference	ILAR-00809	Lenght	108mm	Total Luminous Flux	N/A
Base	N/A	Width	108mm	Luminous Efficacy	N/A
Body Material	Aluminum	Height	140mm	Beam Angle	N/A
Housing Colour	Dark Grey	Packaging Unit	Carton Box 18 pcs	Colour Temperature	N/A
Nominal Lifetime (EOL end of life)	15000h	Gross Weight	13 kg	Colour Rendering Index	N/A
Surface / Recessed	Surface	Volume	42dm ³		
Dimmable	N/A				
Installation	Ceiling				

ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARS		CERTIFICATIONS	
Nominal Wattage	N/A	Energy Label	N/A	2014/30/EU (EMC Directive)	YES
Nominal Voltage	220-240V	Energy Consumption KWH/1000H	N/A	2014/35/EU (LVD Directive)	YES
Operating Frequency	50/60Hz	Type of Protection	IP54	ROHS	YES
Operating Temperature	- 20° C to + 50° C	Protection Class	I	ENEC	NO
Starting Time 100% ON	0.000s	Protecion Class IK (shock resistance)	IK06	Warranty	3 YEARS
ON/OFF Cycles	>15000				

SIZE



BEAM ANGLE

Designed by Aron Light in Portugal. Made in PRC

