

TECHNICAL INFORMATIONS

HARPE DOUBLE

2X 6W 3000K CINZENTO

Luminária LED para aplicação em fachadas com design moderno, chips LED de elevada reprodução, alumínio de fundição injetada, elevados níveis de proteção (IP65 e IK06) e forte resistência à corrosão. Emite luz em duas direcções: para cima (6W) e para baixo (6W).
 Façade LED luminaire with modern design, high reproduction LED chips, die-cast aluminum, high levels of protection (IP65 and IK06) and strong corrosion resistance. Emits light in two directions: up (6W) and down (6W).

Luminaria LED de fachada de diseño moderno, chips LED de alta reproducción, aluminio fundido a presión, altos niveles de protección (IP65 e IK06) y gran resistencia a la corrosión. Emite luz en dos direcciones: arriba (6W) y abajo (6W).




ILAR-00962


REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Reference	ILAR-00962	Lenght	160mm	Total Luminous Flux	900lm
LED Type	LED CREE	Width	Ø65mm	Luminous Efficacy	150lm/W
Body Material	Aluminium body in powder coated	Height	95mm	Beam Angle	2x 16°
Housing Colour	Grey	Packaging Unit	Carton Box 20 pcs	Colour Temperature	3000K
Nominal Lifetime (EOL end of life)	30000H	Gross Weight	-	Colour Rendering Index	>80
Surface / Recessed	Surface	Volume	-		
Dimmable	NO				
Installation	Wall				

ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARS		CERTIFICATIONS	
Nominal Wattage	2x 6W	Energy Label	A+	2014/30/EU (EMC Directive)	YES
Nominal Voltage	220-240V	Energy Consumption KWH/1000H	6 kWh	2014/35/EU (LVD Directive)	YES
Operating Frequency	50/60Hz	Type of Protection	IP65	ROHS	YES
Operating Temperature	- 20° C to + 50° C	Protection Class	Class I	ENEC	NO
Starting Time 100% ON	0.000s	Proteccion Class IK (shock resistance)	IK06	Warranty	3 YEARS
ON/OFF Cycles	>15000				

SIZE



BEAM ANGLE



Designed by Aron Light in Portugal. Made in PRC

