

## TECHNICAL INFORMATIONS

# TAKO

## 2X 5W 3000K BRANCO

Luminária exterior de parede com design moderno, chips LED de elevada reprodução, alumínio de fundição injetada, elevados níveis de proteção (IP54 e IK06) e forte resistência à corrosão. Emite luz em duas direcções: para cima (5W) e para baixo (5W).

Exterior wall luminaire with a modern design, high-reproduction LED chips, die-cast aluminum, high levels of protection (IP54 and IK06) and strong corrosion resistance. Emits light in two directions: up (5W) and down (5W).

Lámpara de pared exterior de diseño moderno, chips LED de alta reproducción, aluminio fundido a presión, altos niveles de protección (IP54 e IK06) y gran resistencia a la corrosión. Emite luz en dos direcciones: arriba (5W) y abajo (5W).




### ILAR-00964


REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Reference	ILAR-00964	Lenght	145mm	Total Luminous Flux	600lm
LED Type	LED CREE	Width	45mm	Luminous Efficacy	120lm/W
Body Material	Die Cast Aluminium	Height	130mm	Beam Angle	2x 104°
Housing Colour	White	Packaging Unit	Carton Box 20 pcs	Colour Temperature	3000K
Nominal Lifetime (EOL end of life)	30000H	Gross Weight	-	Colour Rendering Index	>80
Surface / Recessed	Surface	Volume	-		
Dimmable	NO				
Installation	Wall				

ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARS		CERTIFICATIONS	
Nominal Wattage	2x 5W	Energy Label	A+	2014/30/EU (EMC Directive)	YES
Nominal Voltage	220-240V	Energy Consumption KWH/1000H	5 kWh	2014/35/EU (LVD Directive)	YES
Operating Frequency	50/60Hz	Type of Protection	IP54	ROHS	YES
Operating Temperature	- 20° C to + 50° C	Protection Class	Class I	ENEC	NO
Starting Time 100% ON	0.000s	Proteccion Class IK (shock resistance)	IK06	Warranty	3 YEARS
ON/OFF Cycles	>15000				

### SIZE



### BEAM ANGLE



Designed by Aron Light in Portugal. Made in PRC

