

TECHNICAL INFORMATIONS

PHIL

8W 4500K BRANCO

Aplique de Parede com luz direta integrada em placa de LED SMD.

Wall lamp with direct light integrated into a LED SMDboard.

Aplique de pared con luz directa integrada en placa LED SMD.




ILAR-00955


REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Reference	ILAR-00955	Lenght	160mm	Total Luminous Flux	800lm
LED Brand	LED CREE	Width	51mm	Luminous Efficacy	100lm/W
Body Material	ABS & PC	Height	90mm	Beam Angle	120°
Housing Colour	White	Packaging Unit	32 pc / carton	Colour Temperature	4500K
Nominal Lifetime (EOL end of life)	30000H	Gross Weight	-	Colour Rendering Index	>80
Surface/Recessed	Surface	Volume	-		
Dimmable	NO				

ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARS		CERTIFICATIONS	
Nominal Wattage	8W	Energy Label	A+	2014/30/EU (EMC Directive)	YES
Nominal Voltage	220-240V	Energy Consumption KWH/1000H	8 kwh	2014/35/EU (LVD Directive)	YES
Operating Frequency	50/60Hz	Type of Protection	IP54	CE	YES
Operating Temperature	- 25° C to + 45° C	Protection Class	Class II	ROHS	YES
Starting Time 100% ON	<0.5s	Protecion Class IK (shock resistance)	IK08	Warranty	2 YEARS
ON/OFF Cycles	>30000				

SIZE



BEAM ANGLE



Designed by Aron Light in Portugal. Made in PRC

