



TECHNICAL INFORMATION

FITA LED IP65 9.6W 2700K

Linha de Fitas LED de 24V com um índice de reprodução cromática de 94, ideal para locais de exposição onde a qualidade de cor é um requisito determinante.

24V LED Strip line with a color rendering index of 94, ideal for exhibition venues where color quality is a determining requirement.

Línea de tira de LED de 24V con un índice de reproducción cromática de 94, ideal para lugares de exposición donde la calidad del color es un requisito determinante.




ILAR-00635

REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Reference	ILAR-00635	Length	5000mm	Total Luminous Flux	-
Type	LED ProStrip	Width	10mm	Luminous Efficacy	528lm/mt
Type LED	SMD 2835			LED/MT	60
Nominal Lifetime (EOL end of life)	30000h			Beam Angle	120°
				Colour Temperature	2700K
				Colour Rendering Index	94

ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARS		CERTIFICATIONS	
Power Rated	9.6W	Energy Label	A+	CE	YES
Equivalent Wattage	-	Type of Protection	IP65	ROHS	YES
Lamp Current	-			WARRANTY	2 YEARS
Voltage	24V				
Nominal Voltage	-				
Operating Frequency	-				
Power Factor	>0.95				
Starting Time	-				
Warm - Up Time (60%)	-				
Operating Temperature	-20°C to +40°C				

SIZE



Designed by Aronlight in Portugal. Made in PRC



TECHNICAL INFORMATIONS

FITA LED IP65

9.6W 4000K

Linha de Fitas LED de 24V com um índice de reprodução cromática de 94, ideal para locais de exposição onde a qualidade de cor é um requisito determinante.

24V LED Strip line with a color rendering index of 94, ideal for exhibition venues where color quality is a determining requirement.

Línea de tira de LED de 24V con un índice de reproducción cromática de 94, ideal para lugares de exposición donde la calidad del color es un requisito determinante.



ILAR-00636

REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Reference	ILAR-00636	Length	5000mm	Total Luminous Flux	-
Type	LED ProStrip	Width	10mm	Luminous Efficacy	560lm/mt
Type LED	SMD 2835			LED/MT	60
Nominal Lifetime (EOL end of life)	30000h			Beam Angle	120°
				Colour Temperature	4000K
				Colour Rendering Index	94

ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARS		CERTIFICATIONS	
Power Rated	9.6W	Energy Label	A+	CE	YES
Equivalent Wattage	-	Type of Protection	IP65	ROHS	YES
Lamp Current	-			WARRANTY	2 YEARS
Voltage	24V				
Nominal Voltage	-				
Operating Frequency	-				
Power Factor	>0.95				
Starting Time	-				
Warm - Up Time (60%)	-				
Operating Temperature	-20°C to +40°C				

SIZE



Designed by Aronlight in Portugal. Made in PRC





TECHNICAL INFORMATION

FITA LED IP65

9.6W 6500K

Linha de Fitas LED de 24V com um índice de reprodução cromática de 94, ideal para locais de exposição onde a qualidade de cor é um requisito determinante.

24V LED Strip line with a color rendering index of 94, ideal for exhibition venues where color quality is a determining requirement.

Línea de tira de LED de 24V con un índice de reproducción cromática de 94, ideal para lugares de exposición donde la calidad del color es un requisito determinante.




ILAR-00637

REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Reference	ILAR-00637	Length	5000mm	Total Luminous Flux	-
Type	LED ProStrip	Width	10mm	Luminous Efficacy	584lm/mt
Type LED	SMD 2835			LED/MT	60
Nominal Lifetime (EOL end of life)	30000h			Beam Angle	120°
				Colour Temperature	6500K
				Colour Rendering Index	94

ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARS		CERTIFICATIONS	
Power Rated	9.6W	Energy Label	A+	CE	YES
Equivalent Wattage	-	Type of Protection	IP65	ROHS	YES
Lamp Current	-			WARRANTY	2 YEARS
Voltage	24V				
Nominal Voltage	-				
Operating Frequency	-				
Power Factor	>0.95				
Starting Time	-				
Warm - Up Time (60%)	-				
Operating Temperature	-20°C to +40°C				

SIZE



Designed by Aronlight in Portugal. Made in PRC



TECHNICAL INFORMATIONS

FITA LED IP65

14.4W 2700K

Linha de Fitas LED de 24V com um índice de reprodução cromática de 94, ideal para locais de exposição onde a qualidade de cor é um requisito determinante.

24V LED Strip line with a color rendering index of 94, ideal for exhibition venues where color quality is a determining requirement.

Línea de tira de LED de 24V con un índice de reproducción cromática de 94, ideal para lugares de exposición donde la calidad del color es un requisito determinante.




ILAR-00623

REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Reference	ILAR-00623	Length	5000mm	Total Luminous Flux	-
Type	LED ProStrip	Width	10mm	Luminous Efficacy	792lm/mt
Type LED	SMD 2835			LED/MT	60
Nominal Lifetime (EOL end of life)	30000h			Beam Angle	120°
				Colour Temperature	2700K
				Colour Rendering Index	94

ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARS		CERTIFICATIONS	
Power Rated	14.4W	Energy Label	A+	CE	YES
Equivalent Wattage	-	Type of Protection	IP65	ROHS	YES
Lamp Current	-			WARRANTY	2 YEARS
Voltage	24V				
Nominal Voltage	-				
Operating Frequency	-				
Power Factor	>0.95				
Starting Time	-				
Warm - Up Time (60%)	-				
Operating Temperature	-20°C to +40°C				

SIZE



Designed by Aronlight in Portugal. Made in PRC





TECHNICAL INFORMATION

FITA LED IP65

14.4W 4000K

Linha de Fitas LED de 24V com um índice de reprodução cromática de 94, ideal para locais de exposição onde a qualidade de cor é um requisito determinante.

24V LED Strip line with a color rendering index of 94, ideal for exhibition venues where color quality is a determining requirement.

Línea de tira de LED de 24V con un índice de reproducción cromática de 94, ideal para lugares de exposición donde la calidad del color es un requisito determinante.




ILAR-00624

REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Reference	ILAR-00624	Length	5000mm	Total Luminous Flux	-
Type	LED ProStrip	Width	10mm	Luminous Efficacy	840lm/mt
Type LED	SMD 2835			LED/MT	60
Nominal Lifetime (EOL end of life)	30000h			Beam Angle	120°
				Colour Temperature	4000K
				Colour Rendering Index	94

ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARS		CERTIFICATIONS	
Power Rated	14.4W	Energy Label	A+	CE	YES
Equivalent Wattage	-	Type of Protection	IP65	ROHS	YES
Lamp Current	-			WARRANTY	2 YEARS
Voltage	24V				
Nominal Voltage	-				
Operating Frequency	-				
Power Factor	>0.95				
Starting Time	-				
Warm - Up Time (60%)	-				
Operating Temperature	-20°C to +40°C				

SIZE



Designed by Aronlight in Portugal. Made in PRC



TECHNICAL INFORMATION

FITA LED IP65

14.4W 6500K

Linha de Fitas LED de 24V com um índice de reprodução cromática de 94, ideal para locais de exposição onde a qualidade de cor é um requisito determinante.

24V LED Strip line with a color rendering index of 94, ideal for exhibition venues where color quality is a determining requirement.

Línea de tira de LED de 24V con un índice de reproducción cromática de 94, ideal para lugares de exposición donde la calidad del color es un requisito determinante.




ILAR-00625

REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Reference	ILAR-00625	Length	5000mm	Total Luminous Flux	-
Type	LED ProStrip	Width	10mm	Luminous Efficacy	880lm/mt
Type LED	SMD 2835			LED/MT	60
Nominal Lifetime (EOL end of life)	30000h			Beam Angle	120°
				Colour Temperature	6500K
				Colour Rendering Index	94

ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARS		CERTIFICATIONS	
Power Rated	14.4W	Energy Label	A+	CE	YES
Equivalent Wattage	-	Type of Protection	IP65	ROHS	YES
Lamp Current	-			WARRANTY	2 YEARS
Voltage	24V				
Nominal Voltage	-				
Operating Frequency	-				
Power Factor	>0.95				
Starting Time	-				
Warm - Up Time (60%)	-				
Operating Temperature	-20°C to +40°C				

SIZE



Designed by Aronlight in Portugal. Made in PRC



TECHNICAL INFORMATION

FITA LED IP65

14.4W RGB

Linha de Fitas LED de 24V com um índice de reprodução cromática de 94, ideal para locais de exposição onde a qualidade de cor é um requisito determinante.

24V LED Strip line with a color rendering index of 94, ideal for exhibition venues where color quality is a determining requirement.

Línea de tira de LED de 24V con un índice de reproducción cromática de 94, ideal para lugares de exposición donde la calidad del color es un requisito determinante.



ILAR-00831

REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Reference	ILAR-00831	Length	5000mm	Total Luminous Flux	-
Type	LED ProStrip	Width	10mm	Luminous Efficacy	792lm/mt
Type LED	SMD 5050			LED/MT	60
Nominal Lifetime (EOL end of life)	30000h			Beam Angle	120°
				Colour Temperature	RGB
				Colour Rendering Index	94

ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARS		CERTIFICATIONS	
Power Rated	14.4W	Energy Label	A+	CE	YES
Equivalent Wattage	-	Type of Protection	IP65	ROHS	YES
Lamp Current	-			WARRANTY	2 YEARS
Voltage	24V				
Nominal Voltage	-				
Operating Frequency	-				
Power Factor	>0.95				
Starting Time	-				
Warm - Up Time (60%)	-				
Operating Temperature	-20°C to +40°C				

SIZE



Designed by Aronlight in Portugal. Made in PRC



TECHNICAL INFORMATION

FITA LED IP65

19.2W 2700K

Linha de Fitas LED de 24V com um índice de reprodução cromática de 94, ideal para locais de exposição onde a qualidade de cor é um requisito determinante.

24V LED Strip line with a color rendering index of 94, ideal for exhibition venues where color quality is a determining requirement.

Línea de tira de LED de 24V con un índice de reproducción cromática de 94, ideal para lugares de exposición donde la calidad del color es un requisito determinante.



ILAR-00629

REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Reference	ILAR-00629	Length	5000mm	Total Luminous Flux	-
Type	LED ProStrip	Width	10mm	Luminous Efficacy	95lm/mt
Type LED	SMD 2835			LED/MT	60
Nominal Lifetime (EOL end of life)	30000h			Beam Angle	120°
				Colour Temperature	2700K
				Colour Rendering Index	94

ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARS		CERTIFICATIONS	
Power Rated	19.2W	Energy Label	A+	CE	YES
Equivalent Wattage	-	Type of Protection	IP65	ROHS	YES
Lamp Current	-			WARRANTY	2 YEARS
Voltage	24V				
Nominal Voltage	-				
Operating Frequency	-				
Power Factor	>0.95				
Starting Time	-				
Warm - Up Time (60%)	-				
Operating Temperature	-20°C to +40°C				

SIZE



Designed by Aronlight in Portugal. Made in PRC





TECHNICAL INFORMATION

FITA LED IP65

19.2W 4000K

Linha de Fitas LED de 24V com um índice de reprodução cromática de 94, ideal para locais de exposição onde a qualidade de cor é um requisito determinante.

24V LED Strip line with a color rendering index of 94, ideal for exhibition venues where color quality is a determining requirement.

Línea de tira de LED de 24V con un índice de reproducción cromática de 94, ideal para lugares de exposición donde la calidad del color es un requisito determinante.




ILAR-00630

REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Reference	ILAR-00630	Length	5000mm	Total Luminous Flux	-
Type	LED ProStrip	Width	10mm	Luminous Efficacy	1152lm/mt
Type LED	SMD 2835			LED/MT	60
Nominal Lifetime (EOL end of life)	30000h			Beam Angle	120°
				Colour Temperature	4000K
				Colour Rendering Index	94

ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARS		CERTIFICATIONS	
Power Rated	19.2W	Energy Label	A+	CE	YES
Equivalent Wattage	-	Type of Protection	IP65	ROHS	YES
Lamp Current	-			WARRANTY	2 YEARS
Voltage	24V				
Nominal Voltage	-				
Operating Frequency	-				
Power Factor	>0.95				
Starting Time	-				
Warm - Up Time (60%)	-				
Operating Temperature	-20°C to +40°C				

SIZE



Designed by Aronlight in Portugal. Made in PRC





TECHNICAL INFORMATION

FITA LED IP65

19.2W 6500K

Linha de Fitas LED de 24V com um índice de reprodução cromática de 94, ideal para locais de exposição onde a qualidade de cor é um requisito determinante.

24V LED Strip line with a color rendering index of 94, ideal for exhibition venues where color quality is a determining requirement.

Línea de tira de LED de 24V con un índice de reproducción cromática de 94, ideal para lugares de exposición donde la calidad del color es un requisito determinante.




ILAR-00631

REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Reference	ILAR-00631	Length	5000mm	Total Luminous Flux	-
Type	LED ProStrip	Width	10mm	Luminous Efficacy	1212lm/mt
Type LED	SMD 2835			LED/MT	60
Nominal Lifetime (EOL end of life)	30000h			Beam Angle	120°
				Colour Temperature	6500K
				Colour Rendering Index	94

ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARS		CERTIFICATIONS	
Power Rated	19.2W	Energy Label	A+	CE	YES
Equivalent Wattage	-	Type of Protection	IP65	ROHS	YES
Lamp Current	-			WARRANTY	2 YEARS
Voltage	24V				
Nominal Voltage	-				
Operating Frequency	-				
Power Factor	>0.95				
Starting Time	-				
Warm - Up Time (60%)	-				
Operating Temperature	-20°C to +40°C				

SIZE



Designed by Aronlight in Portugal. Made in PRC

