



TECHNICAL INFORMATIONS


FITA LED SUPER LONG IP20

9.6W 2700K

Linha de Fitas LED de 24V com um índice de reprodução cromática elevada, ideal para locais de exposição onde a qualidade de cor é um requisito determinante.

24V LED Strip line with a high color rendering index, ideal for exhibition venues where color quality is a determining requirement.

Línea de tira de LED de 24V con un índice de reproducción cromática elevado, ideal para lugares de exposición donde la calidad del color es un requisito determinante.




ILAR-01411

REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Reference	ILAR-01411	Length	20000mm	Total Luminous Flux	-
Type	LED ProStrip	Width	10mm	Luminous Efficacy	960 lm/mt
Type LED	SMD 2835	Tape	3M	LED/MT	120
Nominal Lifetime (EOL end of life)	30000h	Cutting Segment	50mm	Beam Angle	120°
				Colour Temperature	2700K
				Colour Rendering Index	>90

ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARS		CERTIFICATIONS	
Power Rated	9.6W	Energy Label	A+	CE	YES
Equivalent Wattage	-	Type of Protection	IP20	ROHS	YES
Lamp Current	-			WARRANTY	2 YEARS
Voltage	24V				
Nominal Voltage	-				
Operating Frequency	-				
Power Factor	>0.95				
Starting Time	-				
Warm - Up Time (60%)	-				
Operating Temperature	-20°C to +40°C				

SIZE



Designed by Aronlight in Portugal. Made in PRC





TECHNICAL INFORMATIONS

FITA LED SUPER LONG IP20

9.6W 4000K

Linha de Fitas LED de 24V com um índice de reprodução cromática elevada, ideal para locais de exposição onde a qualidade de cor é um requisito determinante.

24V LED Strip line with a high color rendering index, ideal for exhibition venues where color quality is a determining requirement.

Línea de tira de LED de 24V con un índice de reproducción cromática elevado, ideal para lugares de exposición donde la calidad del color es un requisito determinante.



ILAR-01412

REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Reference	ILAR-01412	Length	20000mm	Total Luminous Flux	-
Type	LED ProStrip	Width	10mm	Luminous Efficacy	960 lm/mt
Type LED	SMD 2835	Tape	3M	LED/MT	120
Nominal Lifetime (EOL end of life)	30000h	Cutting Segment	50mm	Beam Angle	120°
				Colour Temperature	4000K
				Colour Rendering Index	>90

ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARS		CERTIFICATIONS	
Power Rated	9.6W	Energy Label	A+	CE	YES
Equivalent Wattage	-	Type of Protection	IP20	ROHS	YES
Lamp Current	-			WARRANTY	2 YEARS
Voltage	24V				
Nominal Voltage	-				
Operating Frequency	-				
Power Factor	>0.95				
Starting Time	-				
Warm - Up Time (60%)	-				
Operating Temperature	-20°C to +40°C				

SIZE



Designed by Aronlight in Portugal. Made in PRC





TECHNICAL INFORMATIONS

FITA LED SUPER LONG IP20

9.6W 6000K

Linha de Fitas LED de 24V com um índice de reprodução cromática elevada, ideal para locais de exposição onde a qualidade de cor é um requisito determinante.

24V LED Strip line with a high color rendering index, ideal for exhibition venues where color quality is a determining requirement.

Línea de tira de LED de 24V con un índice de reproducción cromática elevado, ideal para lugares de exposición donde la calidad del color es un requisito determinante.



ILAR-01413

REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Reference	ILAR-01413	Length	20000mm	Total Luminous Flux	-
Type	LED ProStrip	Width	10mm	Luminous Efficacy	960lm/mt
Type LED	SMD 2035	Tape	3M	LED/MT	120
Nominal Lifetime (EOL end of life)	30000h	Cutting Segment	50mm	Beam Angle	120°
				Colour Temperature	6000K
				Colour Rendering Index	>90

ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARS		CERTIFICATIONS	
Power Rated	9.6W	Energy Label	A+	CE	YES
Equivalent Wattage	-	Type of Protection	IP20	ROHS	YES
Lamp Current	-			WARRANTY	2 YEARS
Voltage	24V				
Nominal Voltage	-				
Operating Frequency	-				
Power Factor	>0.95				
Starting Time	-				
Warm - Up Time (60%)	-				
Operating Temperature	-20°C to +40°C				

SIZE



Designed by Aronlight in Portugal. Made in PRC

