

## TECHNICAL INFORMATIONS

# PROJETOR LED TECH

## 600W 5000K

Série profissional de projetores IP66 com 94% de eficiência luminosa, corpo em alumínio fundido de alta intensidade, vidro temperado de alta qualidade que resiste ao impacto e ao atrito.

Professional floodlight series IP66 with 94% luminous efficiency, body of high intensity die-cast aluminum, high quality tempered glass that resist the impact and friction.

Serie profesional de proyectores IP66 con un 94% de eficiencia luminosa, cuerpo de aluminio fundido de alta intensidad, vidrio templado de alta calidad que resiste el impacto y la fricción.



### ILAR-00987

REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Reference	ILAR-00987	Size Piece	529x340x226mm	Total Luminous Flux	78000lm
Led Type	Seoul LED	Luminaire Net Weight	15.3±0.5kg	Luminous Efficacy	130Lm/W
Body Material	Die Cast Aluminium	Item Volume	-	Beam Angle	F06001, F06002, F06003, F06004, F06005, F06006
Body Colour	Grey	Items per Pack	1	Colour Temperature	5000K
Nominal Lifetime	100.000H	Items per Box	1	Colour Rendering Index	>70 (80, 90 optional)
Dimmable	Dimmable and Non-dimmable			Optica Assimétrica	Yes
Intelligent Control	DALI Control				
Driver Brand	Sosen Driver				

ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARDS		CERTIFICATIONS	
Nominal Wattage	600W	Energy Label	A+	CE Directive	YES
Nominal Voltage	100-240V	Energy Consumption KWH/1000H	-	ROHS	YES
ON/OFF Cycles	>15000	Type of Protection	IP66	ENEC	YES
Operating Frequency	50/60Hz	Protection Class	Class II	Warranty	5 YEARS
Power Factor	>0.92	Protecion Class IK (shock resistance)	IK10		
Operating Temperature	- 30° C to + 40° C				
Power Supply	MEAN WELL				

SIZE	BEAM ANGLE

Designed by Aron Light in Portugal. Made in PRC

