

TECHNICAL INFORMATION

LÂMPADA FILAMENTOS A60 GOLD

4W 3000K E27

Lâmpada decorativa de filamentos, com diâmetro de 60mm e acabamento em Dourado.

Decorative filament Bulb, with 60mm diameter and Gold finish.

Bombilla decorativa de filamentos, con diámetro de 60mm y acabado en Dorado.

ILAR-00737



REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Lamp type	Filaments A60 Gold	Diameter	60	Total Luminous Flux	380lm
Lamp Base	E27	Length	108	Luminous Efficacy	110lm/w ±5%
Nominal Lifetime (EOL end of life)	25000h			Beam Angle	360°
Useful Lifetime based on LM80	20000h			Colour Temperature	3000 K
Useful Lifetime based on LM70	20000h			Colour Rendering Index	80
Switching Cycle (times)	50000			Colour Consistency	≤6
Dimmable	No				
Mercury Free	Yes				
ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARS		CERTIFICATIONS	
Power Rated	4W	Energy Label	A+	LM70	YES
Equivalent Wattage	40W	Energy Consumption KWH/1000H	4kwh	LM80	YES
Lamp Current	32mA			LM79	YES
Nominal Voltage	220-240V			TM21	YES
Operating Frequency	50/60Hz			ENEC	YES
Power Factor	0.5				
Starting Time	0.2s				
Warm - Up Time (60%)	0.2s				
Operating Temperature	-20°C to +40°C				

SIZE	BEAM ANGLE

Designed by Aron Light in Portugal. Made in PRC



TECHNICAL INFORMATION

LÂMPADA FILAMENTOS A60 GOLD

4W 2200K E27

Lâmpada decorativa de filamentos, com diâmetro de 60mm e acabamento em Dourado.

Decorative filament Bulb, with 60mm diameter and Gold finish.


Bombilla decorativa de filamentos, con diámetro de 60mm y acabado en Dorado.

ILAR-02488



REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Lamp type	Filaments A60 Gold	Diameter	60	Total Luminous Flux	320lm
Lamp Base	E27	Length	108	Luminous Efficacy	110lm/w ±5%
Nominal Lifetime (EOL end of life)	25000h			Beam Angle	360°
Useful Lifetime based on LM80	20000h			Colour Temperature	2200K
Useful Lifetime based on LM70	20000h			Colour Rendering Index	80
Switching Cycle (times)	50000			Colour Consistency	≤6
Dimmable	No				
Mercury Free	Yes				
ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARS		CERTIFICATIONS	
Power Rated	4W	Energy Label	A+	LM70	YES
Equivalent Wattage	40W	Energy Consumption KWH/1000H	4kwh	LM80	YES
Lamp Current	32mA			LM79	YES
Nominal Voltage	220-240V			TM21	YES
Operating Frequency	50/60Hz				
Power Factor	0.5				
Starting Time	0.2s				
Warm - Up Time (60%)	0.2s				
Operating Temperature	-20°C to +40°C				

SIZE



Designed by Aron Light in Portugal. Made in PRC

