

## TECHNICAL INFORMATION

# CALHA TRIFÁSICA SUPERFÍCIE 1 METRO BRANCA

Calha trifásica para instalação dos diferentes projetores da gama Aronlight. Através das três vias é possível conectar vários projetores na mesma calha permitindo o controle de 3 circuitos de iluminação diferentes.

Para sua instalação é necessário adicionar a fonte de alimentação e as uniões necessárias à instalação.




### ILAR-00590

REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Reference	ILAR-00590	Lenght	1000mm	Total Luminous Flux	-
Led Type	-	Width	35.2mm	Luminous Efficacy	-
Mounting Type	Surface	Height	35.5mm	Beam Angle	-
Body Material	Aluminium	Weight	-	Colour Temperature	-
Housing Colour	White	Cutout	-	Colour Rendering Index	-
Body Shape	-	Packaging Unit	Carton box 1 pcs	Colour Consistency	-
Nominal Lifetime (EOL end of life)	-	Gross Weight	-	UGR	-
Dimmable	-	Volume	-		

ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARS		CERTIFICATIONS	
Nominal Wattage	-	Energy Label	A+	2014/30/EU (EMC Directive)	YES
Nominal Voltage	220-240V	Energy Consumption KWH/1000H	-	2014/35/EU (LVD Directive)	YES
Operating Frequency	50/60Hz	Type of Protection	IP20	ROHS	YES
Power Factor	-	Protection Class	Class I	ENEC	-
Operating Temperature	- 20°C to + 40°C	Protecion Class IK (shock resistance)	-	Warranty	2 YEARS
Starting Time 100% ON	-				
ON/OFF Cycles	-				

### SIZE



Designed by Aronlight in Portugal. Made in PRC



## TECHNICAL INFORMATIONS

# CALHA TRIFÁSICA SUPERFÍCIE 2 METROS BRANCA

Calha trifásica para instalação dos diferentes projetores da gama Aronlight. Através das três vias é possível conectar vários projetores na mesma calha permitindo o controle de 3 circuitos de iluminação diferentes.

Para sua instalação é necessário adicionar a fonte de alimentação e as uniões necessárias à instalação.




### ILAR-00591

REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Reference	ILAR-00591	Lenght	2000mm	Total Luminous Flux	-
Led Type	-	Width	35.2mm	Luminous Efficacy	-
Mounting Type	Surface	Height	35.5mm	Beam Angle	-
Body Material	Aluminium	Weight	-	Colour Temperature	-
Housing Colour	White	Cutout	-	Colour Rendering Index	-
Body Shape	-	Packaging Unit	Carton box 1 pcs	Colour Consistency	-
Nominal Lifetime (EOL end of life)	-	Gross Weight	-	UGR	-
Dimmable	-	Volume	-		

ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARS		CERTIFICATIONS	
Nominal Wattage	-	Energy Label	A+	2014/30/EU (EMC Directive)	YES
Nominal Voltage	220-240V	Energy Consumption KWH/1000H	-	2014/35/EU (LVD Directive)	YES
Operating Frequency	50/60Hz	Type of Protection	IP20	ROHS	YES
Power Factor	-	Protection Class	Class I	ENEC	-
Operating Temperature	- 20°C to + 40°C	Protecion Class IK (shock resistance)	-	Warranty	2 YEARS
Starting Time 100% ON	-				
ON/OFF Cycles	-				

### SIZE



Designed by Aronlight in Portugal. Made in PRC



## TECHNICAL INFORMATIONS

# CALHA TRIFÁSICA SUPERFÍCIE 1 METRO PRETA

Calha trifásica para instalação dos diferentes projetores da gama Aronlight. Através das três vias é possível conectar vários projetores na mesma calha permitindo o controle de 3 circuitos de iluminação diferentes.

Para sua instalação é necessário adicionar a fonte de alimentação e as uniões necessárias à instalação.




### ILAR-01006

REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Reference	ILAR-01006	Lenght	1000mm	Total Luminous Flux	-
Led Type	-	Width	35.2mm	Luminous Efficacy	-
Mounting Type	Surface	Height	35.5mm	Beam Angle	-
Body Material	Aluminium	Weight	-	Colour Temperature	-
Housing Colour	Black	Cutout	-	Colour Rendering Index	-
Body Shape	-	Packaging Unit	Carton box 1 pcs	Colour Consistency	-
Nominal Lifetime (EOL end of life)	-	Gross Weight	-	UGR	-
Dimmable	-	Volume	-		

ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARS		CERTIFICATIONS	
Nominal Wattage	-	Energy Label	A+	2014/30/EU (EMC Directive)	YES
Nominal Voltage	220-240V	Energy Consumption KWH/1000H	-	2014/35/EU (LVD Directive)	YES
Operating Frequency	50/60Hz	Type of Protection	IP20	ROHS	YES
Power Factor	-	Protection Class	Class I	ENEC	-
Operating Temperature	- 20°C to + 40°C	Protecion Class IK (shock resistance)	-	Warranty	2 YEARS
Starting Time 100% ON	-				
ON/OFF Cycles	-				

### SIZE



Designed by Aronlight in Portugal. Made in PRC



## TECHNICAL INFORMATIONS

# CALHA TRIFÁSICA SUPERFÍCIE 2 METROS PRETA

Calha trifásica para instalação dos diferentes projetores da gama Aronlight. Através das três vias é possível conectar vários projetores na mesma calha permitindo o controle de 3 circuitos de iluminação diferentes.

Para sua instalação é necessário adicionar a fonte de alimentação e as uniões necessárias à instalação.




### ILAR-01007

REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Reference	ILAR-01007	Lenght	2000mm	Total Luminous Flux	-
Led Type	-	Width	35.2mm	Luminous Efficacy	-
Mounting Type	Surface	Height	35.5mm	Beam Angle	-
Body Material	Aluminium	Weight	-	Colour Temperature	-
Housing Colour	Black	Cutout	-	Colour Rendering Index	-
Body Shape	-	Packaging Unit	Carton box 1 pcs	Colour Consistency	-
Nominal Lifetime (EOL end of life)	-	Gross Weight	-	UGR	-
Dimmable	-	Volume	-		

ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARS		CERTIFICATIONS	
Nominal Wattage	-	Energy Label	A+	2014/30/EU (EMC Directive)	YES
Nominal Voltage	220-240V	Energy Consumption KWH/1000H	-	2014/35/EU (LVD Directive)	YES
Operating Frequency	50/60Hz	Type of Protection	IP20	ROHS	YES
Power Factor	-	Protection Class	Class I	ENEC	-
Operating Temperature	- 20°C to + 40°C	Protecion Class IK (shock resistance)	-	Warranty	2 YEARS
Starting Time 100% ON	-				
ON/OFF Cycles	-				

### SIZE



Designed by Aronlight in Portugal. Made in PRC

