

TECHNICAL INFORMATIONS

TUBO NEON 360°

20W RGB

Linha de Fitas LED de 24V com um índice de reprodução cromática elevada, ideal para locais de exposição onde a qualidade de cor é um requisito determinante.

24V LED Strip line with a high color rendering index, ideal for exhibition venues where color quality is a determining requirement.

Línea de tira de LED de 24V con un índice de reproducción cromática elevado, ideal para lugares de exposición donde la calidad del color es un requisito determinante.




ILAR-01691

REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Reference	ILAR-01691	Length	5000mm	Luminous Efficacy	1320lm/M
Type	LED Tube	Width	Ø25mm	LM/W	73lm/W
Type LED	SMD2835	Tape	-	Beam Angle	360°
Nominal Lifetime (EOL end of life)	30000h	Cutting Segment	50mm	Colour Temperature	RGB
				Colour Rendering Index	>90

ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARS		CERTIFICATIONS	
Power Rated	20W	Type of Protection	IP67	CE	YES
Equivalent Wattage	-			ROHS	YES
Lamp Current	-			WARRANTY	2 YEARS
Voltage	24V				
Nominal Voltage	-				
Operating Frequency	-				
Power Factor	-				
Starting Time	-				
Warm - Up Time (60%)	-				
Operating Temperature	-20°C to +40°C				

SIZE



ACCESSORIES



CAPS
ILAR-01694



CLIP
ILAR-01695

Designed by Aronlight in Portugal. Made in PRC



TECHNICAL INFORMATIONS

TUBO NEON 360°

20W RGB 10M

Linha de Fitas LED de 24V com um índice de reprodução cromática elevada, ideal para locais de exposição onde a qualidade de cor é um requisito determinante.

24V LED Strip line with a high color rendering index, ideal for exhibition venues where color quality is a determining requirement.

Línea de tira de LED de 24V con un índice de reproducción cromática elevado, ideal para lugares de exposición donde la calidad del color es un requisito determinante.




ILAR-02303

REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Reference	ILAR-02303	Length	10000mm	Luminous Efficacy	1320lm/M
Type	LED Tube	Width	Ø25mm	LM/W	73lm/W
Type LED	SMD2835	Tape	-	Beam Angle	360°
Nominal Lifetime (EOL end of life)	30000h	Cutting Segment	50mm	Colour Temperature	RGB
				Colour Rendering Index	>90

ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARS		CERTIFICATIONS	
Power Rated	20W	Type of Protection	IP67	CE	YES
Equivalent Wattage	-			ROHS	YES
Lamp Current	-			WARRANTY	2 YEARS
Voltage	24V				
Nominal Voltage	-				
Operating Frequency	-				
Power Factor	-				
Starting Time	-				
Warm - Up Time (60%)	-				
Operating Temperature	-20°C to +40°C				

SIZE



ACCESSORIES



CAPS
ILAR-01694



CLIP
ILAR-01695

Designed by Aronlight in Portugal. Made in PRC

