

## TECHNICAL INFORMATIONS

# RGB CCT (2700K-6500K)

## 20W IP20

Linha de Fitas LED de 24V com um índice de reprodução cromática elevada, ideal para locais de exposição onde a qualidade de cor é um requisito determinante.

24V LED Strip line with a high color rendering index, ideal for exhibition venues where color quality is a determining requirement.

Línea de tira de LED de 24V con un índice de reproducción cromática elevado, ideal para lugares de exposición donde la calidad del color es un requisito determinante.




### ILAR-01689

REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Reference	ILAR-01689	Length	5000mm	Luminous Efficacy	70~1555Lm/M
Type	LED ProStrip	Width	12mm	LED / MT	96LEDs/W
Type LED	SMD5050	Tape	3M VHB	LM/W	29~117Lm/w
Nominal Lifetime (EOL end of life)	30000h	Cutting Segment	62.5mm	Beam Angle	120°
				Colour Temperature	RGB CCT (2700K-6500K)
				Colour Rendering Index	>80

ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARS		CERTIFICATIONS	
Power Rated	20W	Type of Protection	IP20	CE	YES
Equivalent Wattage	-			ROHS	YES
Lamp Current	-			WARRANTY	2 YEARS
Voltage	24V				
Nominal Voltage	-				
Operating Frequency	-				
Power Factor	-				
Starting Time	-				
Warm - Up Time (60%)	-				
Operating Temperature	-20°C to +40°C				

### SIZE



Designed by Aronlight in Portugal. Made in PRC





## TECHNICAL INFORMATIONS

# RGB CCT (2700K-6500K)

## 20W IP65

Linha de Fitas LED de 24V com um índice de reprodução cromática elevada, ideal para locais de exposição onde a qualidade de cor é um requisito determinante.

24V LED Strip line with a high color rendering index, ideal for exhibition venues where color quality is a determining requirement.

Línea de tira de LED de 24V con un índice de reproducción cromática elevado, ideal para lugares de exposición donde la calidad del color es un requisito determinante.




### ILAR-01690

REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Reference	ILAR-01690	Length	5000mm	Luminous Efficacy	70~1555Lm/M
Type	LED ProStrip	Width	12mm	LED / MT	96LEDs/W
Type LED	SMD5050	Tape	3M VHB	LM/W	29~117Lm/w
Nominal Lifetime (EOL end of life)	30000h	Cutting Segment	62.5mm	Beam Angle	120°
				Colour Temperature	RGB CCT (2700K-6500K)
				Colour Rendering Index	>80

ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARS		CERTIFICATIONS	
Power Rated	20W	Type of Protection	IP65	CE	YES
Equivalent Wattage	-			ROHS	YES
Lamp Current	-			WARRANTY	2 YEARS
Voltage	24V				
Nominal Voltage	-				
Operating Frequency	-				
Power Factor	-				
Starting Time	-				
Warm - Up Time (60%)	-				
Operating Temperature	-20°C to +40°C				

### SIZE



Designed by Aronlight in Portugal. Made in PRC

