



TECHNICAL INFORMATIONS

PROJECT STRIP IP65

15W 3000K

Linha de Fitas LED de 230V com um índice de reprodução cromática elevada, ideal para locais de exposição onde a qualidade de cor é um requisito determinante.

230V LED Strip line with a high color rendering index, ideal for exhibition venues where color quality is a determining requirement.

Línea de tira de LED de 230V con un índice de reproducción cromática elevado, ideal para lugares de exposición donde la calidad del color es un requisito determinante.



ILAR-01925

REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Reference	ILAR-01925	Length	100M (Roll Strip)	Total Luminous Flux	1500lm/M
Type	LED ProStrip	Width	12x4mm	Luminous Efficacy	120lm/w
Type LED	SMD 2835		Hollow Silicone with 10 mm PCB	LED/MT	120LEDs/W
Nominal Lifetime (EOL end of life)	50000h	Cut-out	100mm	Beam Angle	120°
		Packaging Unit	0 2pcs /carton	Colour Temperature	3000K
				CRI	>80
ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARS		CERTIFICATIONS	
Power Rated	15W/M	Energy Label	A+	CE	YES
Equivalent Wattage	-	Type of Protection	IP65	ROHS	YES
Lamp Current	-	Protecion Class IK (shock resistance)	IK10	WARRANTY	3 YEARS
Voltage	230V				
Nominal Voltage	-				
Operating Frequency	-				
Power Factor	>0.90				
Starting Time	-				
Warm - Up Time (60%)	-				
Operating Temperature	-20°C to +40°C				

Designed by Aronlight in Portugal. Made in PRC





TECHNICAL INFORMATIONS

PROJECT STRIP IP65

15W 4000K

Linha de Fitas LED de 230V com um índice de reprodução cromática elevada, ideal para locais de exposição onde a qualidade de cor é um requisito determinante.

230V LED Strip line with a high color rendering index, ideal for exhibition venues where color quality is a determining requirement.

Línea de tira de LED de 230V con un índice de reproducción cromática elevado, ideal para lugares de exposición donde la calidad del color es un requisito determinante.



ILAR-01926

REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Reference	ILAR-01926	Length	100M (Roll Strip)	Total Luminous Flux	1500lm/M
Type	LED ProStrip	Width	12x4mm	Luminous Efficacy	120lm/w
Type LED	SMD 2835		Hollow Silicone with 10 mm PCB	LED/MT	120LEDs/W
Nominal Lifetime (EOL end of life)	50000h	Cut-out	100mm	Beam Angle	120°
		Packaging Unit	0 2pcs /carton	Colour Temperature	4000K
				CRI	>80
ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARS		CERTIFICATIONS	
Power Rated	15W/M	Energy Label	A+	CE	YES
Equivalent Wattage	-	Type of Protection	IP65	ROHS	YES
Lamp Current	-	Protecion Class IK (shock resistance)	IK10	WARRANTY	3 YEARS
Voltage	230V				
Nominal Voltage	-				
Operating Frequency	-				
Power Factor	>0.90				
Starting Time	-				
Warm - Up Time (60%)	-				
Operating Temperature	-20°C to +40°C				

Designed by Aronlight in Portugal. Made in PRC





TECHNICAL INFORMATIONS

PROJECT STRIP IP65

15W 6000K

Linha de Fitas LED de 230V com um índice de reprodução cromática elevada, ideal para locais de exposição onde a qualidade de cor é um requisito determinante.

230V LED Strip line with a high color rendering index, ideal for exhibition venues where color quality is a determining requirement.

Línea de tira de LED de 230V con un índice de reproducción cromática elevado, ideal para lugares de exposición donde la calidad del color es un requisito determinante.



ILAR-01927

REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Reference	ILAR-01927	Length	100M (Roll Strip)	Total Luminous Flux	1500lm/M
Type	LED ProStrip	Width	12x4mm	Luminous Efficacy	120lm/w
Type LED	SMD 2835		Hollow Silicone with 10 mm PCB	LED/MT	120LEDs/W
Nominal Lifetime (EOL end of life)	50000h	Cut-out	100mm	Beam Angle	120°
		Packaging Unit	0 2pcs /carton	Colour Temperature	6000K
				CRI	>80
ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARS		CERTIFICATIONS	
Power Rated	15W/M	Energy Label	A+	CE	YES
Equivalent Wattage	-	Type of Protection	IP65	ROHS	YES
Lamp Current	-	Protecion Class IK (shock resistance)	IK10	WARRANTY	3 YEARS
Voltage	230V				
Nominal Voltage	-				
Operating Frequency	-				
Power Factor	>0.90				
Starting Time	-				
Warm - Up Time (60%)	-				
Operating Temperature	-20°C to +40°C				

Designed by Aronlight in Portugal. Made in PRC

