

TECHNICAL INFORMATION

PRADO PRO

20W 3CCT

Projektor de calha orientável com tecnologia de alumínio em fundição injetada, elevado rigor geométrico e acabamentos de alta qualidade. Permite a escolha de temperatura de cor através de switch na parte traseira do projetor.

Orientable Track Light with die-cast aluminium technology, high geometric accuracy and high precision surface finish. Allows the choice of color temperature through a switch on the back of the luminaire.

Proyector de carril orientable con tecnología de aluminio en fundición inyectada, alto rigor geométrico y acabados de alta calidad. Permite la elección de la temperatura de color a través de un interruptor en la parte posterior de la luminaria.




ILAR-02870

REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Reference	ILAR-02870	Length	130mm	Total Luminous Flux	Max. 1900lm
Mounting Type	4Wire 3Phase Tracklight	Width	Ø65mm	Luminous Efficacy	Max. 95lm/w
Body Material	AL1070 Aluminium			Beam Angle	36°
Housing Colour	Black			Colour Temperature	3CCT (3000K, 4000K, 6000K)
Nominal Lifetime (EOL end of life)	50.000h			Colour Rendering Index	>90
Dimmable	No				

ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARDS		CERTIFICATIONS	
Nominal Wattage	20W	Type of Protection	IP20	2014/30/EU (EMC Directive)	YES
Nominal Voltage	220-240V	Protection Class	Class II	2014/35/EU (LVD Directive)	YES
Operating Frequency	50/60Hz	Protection Class IK (shock resistance)	IK03	ROHS	YES
Power Factor	0.95			Warranty	3 YEARS
Operating Temperature	- 30°C to + 40°C				

SIZE



ACCESSORIES



ILAR-02874

RING+HONEYCOMB for PRADO PRO 20W BLACK

Designed by Aronlight in Portugal. Made in PRC



TECHNICAL INFORMATION

PRADO PRO

20W 3CCT

Projektor de calha orientável com tecnologia de alumínio em fundição injetada, elevado rigor geométrico e acabamentos de alta qualidade. Permite a escolha de temperatura de cor através de switch na parte traseira do projetor.

Orientable Track Light with die-cast aluminium technology, high geometric accuracy and high precision surface finish. Allows the choice of color temperature through a switch on the back of the luminaire.

Proyector de carril orientable con tecnología de aluminio en fundición inyectada, alto rigor geométrico y acabados de alta calidad. Permite la elección de la temperatura de color a través de un interruptor en la parte posterior de la luminaria.




ILAR-02871

REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Reference	ILAR-02871	Lenght	130mm	Total Luminous Flux	Max. 1900lm
Mounting Type	4Wire 3Phase Tracklight	Width	Ø65mm	Luminous Efficacy	Max. 95lm/w
Body Material	AL1070 Aluminium			Beam Angle	36°
Housing Colour	White			Colour Temperature	3CCT (3000K, 4000K, 6000K)
Nominal Lifetime (EOL end of life)	50.000h			Colour Rendering Index	>90
Dimmable	No				

ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARS		CERTIFICATIONS	
Nominal Wattage	20W	Type of Protection	IP20	2014/30/EU (EMC Directive)	YES
Nominal Voltage	220-240V	Protection Class	Class II	2014/35/EU (LVD Directive)	YES
Operating Frequency	50/60Hz	Protection Class IK (shock resistance)	IK03	ROHS	YES
Power Factor	0.95			Warranty	3 YEARS
Operating Temperature	- 30°C to + 40°C				

SIZE



ACCESSORIES



ILAR-02875
RING+HONEYCOMB for PRADO PRO 20W WHITE

Designed by Aronlight in Portugal. Made in PRC

