

UT333/UT333BT temperature humidity meters can measure, process data, and display results on LCD. UT333BT can transfer measurement data through Bluetooth to UNI-T's custom mobile APP (iENV2.0) for further analysis, storage, and data export. iENV2.0 can be downloaded from Google Play, Apple Store or UNI-T's website by searching 'iENV2.0'.



UT333BT

Specifications	UT333	UT333BT
Certificates	CE, UKCA	
Temperature range	-10°C~60°C/14°F~140°F	-10°C~60°C/14°F~140°F
Temperature accuracy	±1°C/±2°F	±1°C/±2°F
Temperature resolution	0.1°C/0.2°F	0.1°C/0.2°F
Humidity range	0%RH~100%RH	0%RH~100%RH
Humidity accuracy	±5%RH	±5%RH
Humidity resolution	0.1%RH	0.1%RH
Sampling rate	1/s	1/s
Bluetooth APP		√
Overload indication	√	√
Auto power off	5 min	5 min
Low battery indication	3V~3.5V	3V~3.5V

Features	
MAX/MIN	°C/°F selection
Data hold	LCD backlight

Characteristics	
Standard accessories	Batteries, English manual
Power	1.5V battery (R03) x 3
Display	32 x 26mm
Product size	155 x 50 x 28mm
Product net weight	102g
Standard individual packing	Blister
Standard quantity per carton	UT333: 40pcs; UT333BT: 20pcs
Standard carton measurement	UT333: 505 x 330 x 280mm; UT333BT: 332 x 262 x 290mm
Standard carton gross weight	UT333: 8kg; UT333BT: 4.2kg